

THERMAL IMAGING CAMERA METER LTMET14-3



THERMAL IMAGING CAMERA METER LTMET14-3

LTMET14-3 THERMAL IMAGING CAMERA METER



SPECIFICATIONS

Model	LTMET14-3
Display screen	3.5 "full angle TFT display screen
Infrared image resolution	320x240
visible image resolution	300,000 pixel
Field angle/shortest focus length	56°x 42°/ 0.15 m
Thermal sensitivity	0.07 °C
Temperature measurement range	-20°C to 450°C (-4°F to 854°F)
Measurement accuracy	± ≤100 °C ±2 °C ; 100-300 °C ± 2 % ; ≥300 °C ± 3 %
Emissivity	Adjustable from 0.01 to 1.0
Frame rate of thermal images	9 Hz
Wavelength coverage	8-14 um
Focus mode	Fixed
Color palette	Rainbow, iron oxide red, cold color, black & white, white & black
View option	The integration of thermal image with 25 % step length and visible image.
Storage medium	Built-in 3G (above 20 thousand image stored)
File format	JPG
USB	Micro USB 2.0
Power supply	Built-in rechargeable 26650 battery
Automatic power-off time	Selectable: 5 minutes/20 minutes/not power off automatically
Product size (length x width x height)	97 mm x 129 mm x 256 mm
Work temperature	0 °C to 45 °C
Storage temperature	- 20 °C to 60 °C
Relative humidity	< 85 % RH



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com