

MULTI-PARAMETER ANALYZER LTMET16-12



MULTI-PARAMETER ANALYZER LTMET16-12

LTMET16-12 MULTI-PARAMETER ANALYZER



Product Image Coming Soon

SPECIFICATIONS

Model	LTMET16-12
DC Voltage	
300 mV	$\pm (0.1\%+5)$
3 V/30 V/300 V	$\pm (0.05\%+5)$
1000 V	$\pm (0.1\%+5)$
DC Current	
300 μ A/3 mA/30 mA/300 mA	$\pm (0.5\%+10)$
10 A	$\pm (1.2\%+50)$
Resistance	
300 Ω /3 k Ω /30 k Ω /300 k Ω	$\pm (0.5\%+10)$
3 M Ω /30 k Ω /300 k Ω	$\pm (0.8\%+10)$
30 M Ω	$\pm (1.5\%+10)$
300 M Ω	$\pm (3.0\%+10)$
Capacitance	
30 nF/300 nF/3 μ F/30 μ F	$\pm (3.0 \% + 5)$
300 μ F/3 mF	$\pm (4.0 \% + 5)$
30 mF	$\pm (10.0 \% + 5)$
300 mF	$\pm (20.0\%+5)$
Frequency	
10 ~300 Hz	$\pm (0.01.0 \%+5)$
Duty	
0.1 % ~ 99 %	$\pm (2.0 \%+5)$
Display	
	30000 Counts T-RMS
Auto / Manual Range	Yes
Bargraph Display	Yes
Relative Measurement	Yes
True RMS	Yes

MAX/IMIN	Yes
USB Interface	Yes
Data Hold	Yes
Diode Test	Yes
Transistor	Yes
Continuity	Yes
Capacitance Test	Yes
AC+DC Voltage Measurement	Yes
Back Light	Yes
Power Supply	4x1.5 VAA Batteries
359.5 g(Without Battery)	Size
195x93x54 mm	Safety Level



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com