

GLOSS METER LTMET17-7



GLOSS METER LTMET17-7

LTMET17-7 GLOSS METER



SPECIFICATIONS

Model	LTMET17-7
Measuring Angle	20°/60°/85°
Measuring Area (mm)	20°:9x10 60°:9x15 85°:5x38
Measuring Range	20°: 0-2000 GU 60°: 0-1000 GU 85°: 0-160 GU
Division Value	0.1 GU
Measuring Time	0.5 s
Repeatability	0~100GU:±0.2GU 100-2000GU:±0.2GU U %
Accurate	Conform with JJG696 first grade requirements of gloss meter
Auto Power-off Time	Within 30 s-120 s
Long-time Calibration	Automatically finished calibration
Language	Chinese English
Storage	35000(Basic mode SStatistic mode :15000; Continuous mode : 10000; QC mode: 10000)
Display	3.3 inch black and white screen
Size	160x52x84 mm
Weight	About 300 g
Power Supply	1 pc dry-cell battery(can measure 10000 times) or use USB Charge
Interface	USB & Bluetooth
PC Software	GQC6 QC software for quality report and more extended functions
Operation Temperature Range	0~40 °C 32~104 °F)
Storage Temperature Range	- 20~50 °C (-4~122 °F)
Humidity Range	< 85% RH, without condensation
Standard Accessories	User manual, calibration plate,USB cable, user manual, QC software (Download official website) calibration plate,user manual
Optional Accessories	Miniature printer



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com