4°C BLOOD BANK REFRIGERATOR LTREF8-2



4°C BLOOD BANK REFRIGERATOR LTREF8-2

Used in Immunohematology Department, Blood Bank, Laboratory, Research, Medical, Pharmaceutical. Also known as Laboratory Blood Bank Refrigerator.

LTREF8-2 4°C BLOOD BANK REFRIGERATOR

Microprocessor-based temperature controller, Temperature range is $4\pm1^{\circ}$ C Large screen LCD display of temperature, display accuracy of +/- 0.1°C

Automatic temperature control, Defrost automatic

Audible and visual alarm

Upright type, Exterior made from painted steel plate, Inside is stainless steel. Four units Caster are mounted under the bottom

Three-layer glass door with heater around to prevent ice leak., and lockable

Interior fluorescent light

4 Inner shelves (wire plastics)

Forced air circulation system

Danfoss compressor and EBM fan motors from Germany

The high-effective air-cooled condenser and the fin-type evaporator

Two in depend refrigeration system, automatic cut-in when other one damage

Standard: Temperature printer

Optional: Chart recorder, Blood storage basket



SPECIFICATIONS

Model	LTREF8-2
Capacity	268 L
Temperature Range	+4°C, +2~+10°C
Refrigerant	R134a, CFC free
Refrigeration System	International famous compressor and Germany EBM fan motor.
Defrost Method	No frost design
Controller	Microprocessor Controller with LCD Display
Control Sensor	2
Alarms	High & low temperature alarm, Sensor failure alarm, Door open alarm, Power off alarm, System failure alarm
Shelves	4 stainless steel drawers
External Size	628x700x1662 mm
Package Size	775x780x1810 mm
Optional Accessories	Chart Recorder, Touch screen, Blood storage basket
Weight	148 Kgs
Input/Average Power	400W/200W
Power Supply	220V,50/ 60Hz, 110V,50/60Hz, 220V,50Hz/ 120V,60Hz

labtare.com 2



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com