

4°C BLOOD BANK REFRIGERATOR LTREF8-6



4°C BLOOD BANK REFRIGERATOR LTREF8-6

Used in Immunohematology Department, Blood Bank, Laboratory, Research, Medical, Pharmaceutical.

Also known as Laboratory Blood Bank Refrigerator.

LTREF8-6 4°C BLOOD BANK REFRIGERATOR

Microprocessor controller, Temperature range is $4 \pm 1^\circ\text{C}$

Large screen LCD display of temperature, display accuracy is 0.1°C

Audible and visual alarm

Upright type, Exterior made from painted steel plate, Inside is 304 stainless steel. Four units Caster are mounted under the bottom

Three-layer glass door with heater around to prevent ice leak, inert gas inside and lockable

Interior fluorescent light

Forced air circulation system

The high-effective air-cooled condenser and the fin-type evaporator

Standard: Temperature printer

Optional: Chart recorder, Blood storage basket



SPECIFICATIONS

| | |
|----------------------|--|
| Model | LTREF8-6 |
| Capacity | 950 L |
| Temperature Range | $+4^\circ\text{C}$, $+2 \sim +10^\circ\text{C}$ |
| Refrigerant | R134a, CFC free |
| Refrigeration System | International famous compressor and Germany EBM fan motor. |
| Defrost Method | No frost design |
| Controller | Microprocessor Controller with LCD Display |
| Control Sensor | 2 |
| Alarms | High & low temperature alarm, Sensor failure alarm, Door open alarm, Power off alarm, System failure alarm |
| Shelves | Adjustable 8 units steel wire shelves |
| External Size | 780x1200x1894 mm |
| Package Size | 885x1300x2200 mm |
| Optional Accessories | Chart Recorder, Touch screen, Blood storage basket |
| Weight | 125 Kgs |
| Input/Average Power | 700W/350W |
| Power Supply | 220V,50/ 60Hz, 110V,50/60Hz, 220V,50Hz/ 120V,60Hz |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com