

# GLASSWARE WASHER LTWSH8-3



# GLASSWARE WASHER LTWSH8-3

Used in University , Research institution, Pharmaceutical, Chemical industry, Microbiology Lab.  
Also known as Washer Disinfecter.

## LTWSH8-3 GLASSWARE WASHER

High efficient cleaning system, designed with European reliable pump, optimized spray arm and nozzles and self-cleaning program.

Rapid and efficient drying system, designed with independent air heater, HEPA filter and drying process

Water heating temperature can reach 99°C , while hot air drying temperature can reach 120°C

Professional configuration design-stainless steel for corrosion resistance; reinforced glass window mounted to achieve a clear view on washing process

PLC touch screen control with present 12 programs and 99 customized programs

Safety protection-electronic security door lock to prevent unexpected door opening , water & drying air temperature dual control and equipped with emergency switch.



## SPECIFICATIONS

Model	LTWSH8-3
Capacity	320 L
Water Consumption Cycle	22 L
Inlet Water Pressure	0.3~0.8 Mpa
Noise	≤ 55 dB
Material	Internal Material: SS316, Outer Material:SS304
Overall Power Consumption	6/17 KW
Power Consumption- Water Washing	1.5 KW
Power Consumption- Water Heating	5/15 KW
Power Consumption-Drying	3.6 KW
Power Supply	AC220 V, 50 Hz , 380 V ,50Hz (Standard) 110V , 60 Hz (Optional)
Cleaning Rack	3 pcs
Standard Cleaning Rack	BKIR36 x 3
Standard Accessories	USB interface, One Bucket RBS A 156 leaner (1L), One Bucket RBS A 375 neutralizer (1L)
Optical Accessories	Cleaning Racks
Washer Chamber Size (WxDxH)	600x629x820 mm
External Size (WxDxH)	690x790x1970 mm
Package Size (WxDxH)	790x940x2100 mm
Gross Weight	320 kg



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)