

TUBE ROLLER MIX16-70



TUBE ROLLER MIX16-70

DC brushless motor provides reliable and quiet running, maintenance free and can be used in cold rooms or in incubators, Majorly used in Industrial, Clinical Laboratories, Academic Facilities, Environmental Applications, Food Technology and Wastewater Facilities.

Used in Industrial, Clinical Laboratories, Academic Facilities, Environmental Applications, Food Technology, Wastewater Facilities.

Also known as Tube Rotator, Rotator, Laboratory Rotator.

MIX16-70 TUBE ROLLER

The rotator comes with a rotisserie type design

Digital control speed and allowing procedures to be accurate

LCD displays timer

End-over-end or rolling action, gives gentle but effective mixing

Adjustable speed range of 10 to 70 rpm

Used with a wide variety of accessories

Continuous and timed quiet operation



SPECIFICATIONS

Model	MIX16-70
Speed Range	10-70 rpm
Permissible Relative Humidity	0.8
Tilt Angle (°)	90
Operation	Continuous/ timed operation
Timer	Yes
Timing Range	1-1199 min
Overall Dimension	510Dx190Wx260H mm
Motor Type	DC motor
Protection Class	IP21
Display	LCD
Weight	8 kg
Power	40 W
Power Supply	100-240V, 50/60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52511	Rotisserie accessory	For 1.5ml x 48 centrifuge tubes held horizontally
LS52524	Rotisserie accessory	For 15ml x 24 centrifuge tubes held horizontally
LS52537	Rotisserie accessory	For 50ml x 24 centrifuge tubes held horizontally
LS52550	Rotisserie accessory	For 1.5ml x 32 centrifuge tubes held vertically

LS52563	Rotisserie accessory	For 15ml x 16 centrifuge tubes held vertically
LS52576	Rotisserie accessory	For 50ml x 16 centrifuge tubes held vertically



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com