

VACUUM DRYING OVEN OVE22-23M



VACUUM DRYING OVEN OVE22-23M

Vacuum ovens are very versatile pieces of equipment with applications in laboratory research, engineering, and industry. The low pressure environment also minimizes oxidation during drying. A rugged, high quality pressure chamber, gasket seals, and pump are features to look for, as well as convenient, programmable controls and a computer interface.

Used in Biochemical, Pharmaceutical, Healthcare, Agricultural, Environmental protection, disinfection, Sterilization, Drying, Roasting, Laboratory, Research, engineering, Industry,.

Also known as Vacuum Oven, Laboratory Vacuum Oven.

OVE22-23M VACUUM DRYING OVEN

10 segment programmable microcomputer PID intelligent control system

Vacuum degree display: Pointer display

Vacuum degree control: Manual control

Imported environmental protection type insulation materials

SUS304 stainless steel Interior materials

ALLHEATTM: Cavity Warm-up Technology

Imported Temperature and Vacuum Sensor

Optional accessories: Portable printer/ALLSENSTM software, LCD touch screen controller, Programmable multi-stage controller



SPECIFICATIONS

| | |
|----------------------------|--------------------------|
| Model | OVE22-23M |
| Capacity | 23 L |
| Temperature Range | RT+5~250°C |
| Ambient Temperature | 10~30°C |
| Temperature Fluctuation | ±1(10°C~240°C) |
| Temperature Resolution | ±0.1°C |
| Ambient Humidity | <70% |
| Timer Range | 0~99h or 0~9999min |
| Internal Dimension (WxDxH) | 285x258x315 mm |
| Overall Dimension (WxDxH) | 695x545x480 mm |
| Shelves | 2 |
| Weight | 33 kg |
| Power | 800 W |
| Power Supply | Single phase AC220V/50Hz |



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com