

# VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE PIP11-00050E



# VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE PIP11-00050E

Single Channel Pipette is the new standard for microliter measurements. It is top of the line micropipette that is ergonomically designed and easily adjustable. They are commonly used in laboratory, research, chemistry, biology, forensic, pharmaceutical, and drug discovery labs to transfer small quantities of liquid.

Used in Environmental Sciences, Laboratory, Research, Liquid Handling Task, Institutes, Pharmaceutical, Industrial, Microbiology, Chemistry, Biology, Medical, Plasmid Purification.

Also known as Micropipette, Laboratory Single Channel Pipette, Laboratory Micropipette.

## PIP11-00050E VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE

Large central pipetting button and separate ejection function

True one-handed operation for both right-and left-handers

Completely autoclavable at 121°C(20min)

Volume-change protection

4-Position volume display, always clearly visible externally

Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)

Corrosion-resistant piston and ejector

Color-coded for easy selection of the right tip



### SPECIFICATIONS

Model	PIP11-00050E
Autoclavable	Ejector 121°C
Volume	5-50 µl
Increment (µl)	0.05
Unit	20



**Labtare USA**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)