

COOLED SHAKING INCUBATOR SHA15-300



COOLED SHAKING INCUBATOR SHA15-300

Highly efficient insulation guarantees homogeneous temperature dispersion as well as reproducible cultivation results and combines uniform, reliable performance with low energy consumption. Suitable for cell culturing, solubility studies, sample preparation, water analysis, BOD measurement, plating and breeding experiments in research institutions, universities and colleges.

Used in Cell Culturing, Cell Aeration, Solubility Studies, Sample Preparation, Water Analysis, BOD Measurement, Plating, Breeding Experiments, Research Institutions, Universities, Colleges.

Also known as Cooled Shaking Incubator, Shaker Incubator, Laboratory Cooled Shaking Incubator.

SHA15-300 COOLED SHAKING INCUBATOR

Microprocessor controller

Stainless steel interior and Electrostatic sprayed exterior

LCD display



SPECIFICATIONS

Model	SHA15-300
Speed Range	20-300 rpm
Standard Capacity	250mlx54
Temperature	4°C~60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Shaking Speed Accuracy	±1 rpm
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	1
Platform Dimension	730x460 ml
Overall Dimension	980x820x1335 ml
Display	LCD
Weight	240 kg
Power	1250 W
Power Supply	220V, 60Hz



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com