

INCUBATOR SHAKER SHA28-0300



INCUBATOR SHAKER SHA28-0300

In Incubator Shaker, the constant agitation with uniform amplitude provides the optimum oxygen transfer to the cultures, leading to better and consistent yield. A variety of platforms and different laboratory accessories permits configuration to fulfill your demands.

Used in Cell Cultures, Cell Aeration, Microbiology, Increasing Solubility Rates, Metabolism Studies, Bacterial Cultures, Bacteriology.

Also known as Laboratory Incubator Shaker, Incubator Shaker.

SHA28-0300 INCUBATOR SHAKER

Encryption lock for operation parameters

The micro processing chip frequency control

With the timing function of 1 min to 99.9 hrs, the remaining time is displayed on LCD

Audible alarm

Motor overheating protection device

The unique three-dimensional eccentric wheel driving mechanism

With operating parameter memory function

Microprocessor PID controller

The AC induction motor drive, wide speed, constant torque, constant speed, no carbon brush, long life, maintenance free heating parts

Automatically cut off the heating power when overheating



SPECIFICATIONS

Model	SHA28-0300
Speed Range	20-300 rpm
Standard Capacity	250mlx24
Temperature	RT+5-60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	2
Platform Dimension	500x350 mm
Overall Dimension	700x665x1350 mm
Display	LCD
Weight	150 kg
Power	720 W
Power Supply	220V, 50/60Hz



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com