

-10°C TO -25°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER ULT13-485



-10°C TO -25°C ULTRA LOW TEMPERATURE

UPRIGHT FREEZER ULT13-485

Engineered for storage of number of samples like test samples and plasma to biologicals, enzymes for genetic research, sensitive materials and temperature. Features like low energy consumption, low noise level, low heat dissipation and safety towards audible alarm for high/ low temperature makes this product perfect.

Used in Laboratories, Routine Cold Storage, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

ULT13-485 -10°C TO -25°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER

Chemically stable, CFC-Free, environmentally, safe refrigerant

High density CFC-Free urethane foam insulation for rigidity and stable storage temperature

Microprocessor control, digital display adjustable

LED digital display

Audible and visible alarm

Controller password protect function to avoid change running parameter randomly

Independent inner door to avoid more cooling leaking out, and provide more stable internal temperature performance

Upright side door with built-in handle for easy-opening; limit door hinge to prevent collision when door open

Lockable caster design for customer to move as needed



SPECIFICATIONS

| | |
|----------------------|---|
| Model | ULT13-485 |
| Capacity | 485 L |
| Temperature Range | -10°C to -25°C |
| Ambient Temperature | 10°C ~ +32°C |
| Defrosting | Manual |
| Cooling Type | Direct Cooling |
| Insulation Material | PURF |
| Refrigerant | HC-R290 |
| Internal Dimension | 1455x525x665 mm |
| Overall Dimension | 1655x755x915 mm |
| Package Size | 1710x885x1020 mm |
| Exterior | Color Sprayed steel |
| Controller | Microprocessor, Digital display |
| Sensor | NTC |
| Compressor Brand/QTY | CUBIGELN/1 |
| Alarm | High/low temperature, Power off, Sensor malfunction, Temperature controller malfunction |
| Standard Accessories | Caster Optional accessories: Test hole |
| Weight (Net/Gross) | 124 / 138 kg |

| | |
|---------------------------------|------------|
| Rated Power | 295 W |
| Power Consumption (Kwh/24hrs) | 3.45 |
| Power Supply | 220V, 50Hz |



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com