

-10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER ULT34-838A



-10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER ULT34-838A

Designed with microprocessor-based temperature controller and used for dependability and sample protection on daily basis. High-quality proven components with energy-efficient refrigeration design and majorly used in hospitals, clinics, blood banks and research institutes for preservation of plasma, tissue cultures and microbial cultures. Used in Preservation Of Plasma, Microbial Cultures, Tissues, Cell Lines, Clinical, Industrial, Research. Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

ULT34-838A -10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER

- Settable high temperature and low temperature alarms
- Automatic clean-filter alarm and sensor error alert
- Adjustable storage shelf height
- Unique insulated inner door design for four separate storage compartments to minimize frost buildup inside the chamber
- Specialized control system design for a well-balanced operation of cascade refrigeration system
- Audible and visible alarm
- Door open feature standard and USB port for temperature data downloading standard on upright models
- Remote alarm contacts
- Unique door seal design for the minimum loss of cold temperature during a door opening
- High performance VIP insulation panels to minimize cabinet heat gain and to improve temperature stability



SPECIFICATIONS

Model	ULT34-838A
Capacity	838 L
Temperature Range	-40°C to -86°C
Ambient Temperature	10°C ~ +32°C
Temperature Increment	1°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	Mixed-gas
Internal Dimension	894x718x1310 mm
Overall Dimension	1160x1172x1994.5 mm
Package Size	1212x1098x2185 mm
Drawers/Shelves	Stainless steel shelf/3
Interior	Stainless steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display

Sensor	PTC
Compressor Brand/QTY	SECOP/2
Evaporator	Submerged coil evaporator
Evaporator Material	Copper tube evaporator
Condenser	Copper tube and finned
Noise Level	55 db
Alarm	High/low temperature, Power off, Sensor malfunction, Abnormal voltage, Filter screen check, Thermostat failure, Low battery, Condensor clean, High ambient temperature, Door ajar
Standard Accessories	Castor, Inner doorx2, Test hole 1/25 mm, USB port
Optional Accessories	Data logger, CO2 backup system, LN2 backup system, Temperature recorder, Storage racks and storage box
Weight (Net/Gross)	391 / 424 kg
Rated Power	840 W
Power Consumption (Kwh/24hrs)	14.5
Rated Current A	6.5
Power Supply	220V, 50Hz



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com