

MEDICAL AUTOMATIC GLASSWARE WASHERS



MEDICAL AUTOMATIC GLASSWARE WASHERS

Used in Medical, Pharmaceutical, Research institutes, Chemical industry, Microbiology Lab, University.
Also known as Washer Disinfectors.

LTWSH9 GLASSWARE WASHER

Two toughened glass doors, prevent cross infection

Color LCD touch screen, advanced programmable control system with six standard programs

High efficient cleaning system, with rotary nozzles in top, bottom and among the shelves to make sure that the spray liquid can contact the surface of devices completely

High efficient drying system with HEPA filter, can clean and dry the inner of tubular things

Thermal disinfection, water heating system can make sure the water temperature keep above 93°C to reach the international disinfecting efficiency level.



SPECIFICATIONS

Model	LTWSH9-1	LTWSH9-2	LTWSH9-3
Capacity	220 L	320 L	420 L
Water Consumption Cycle	22 L	24 L	26 L
Inlet Water Pressure	0.03~0.8 Mpa		
Noise	< 60 dB		
Material	Stainless Steel		
Overall Power Consumption	17 KW		
Power Consumption- Water Washing	1.5 KW		
Power Consumption- Water Heating	15 KW		
Power Consumption-Drying	3.6 KW		
Power Supply	380 V , 50 Hz (Standard) , 110 V , 60 Hz (Optional)		
Standard Cleaning Rack	BK01-220x1 (4 layers)	BK01-320x1 (5 layers)	BK01-420x1 (5 layers)
Standard Accessories	Built-in printer, One Bucket RBS A 156 leaner (1 L), One bucket RBS A 375 neutralizer (1 L)		
Optical Accessories	Trolley (BKO 1)		
Washer Chamber Size (WxDxH)	600x629x658 mm	600x629x820 mm	688x700x703 mm
External Size (WxDxH)	960x800x1880 mm	960x800x2030 mm	1100x930x2085 mm
Package Size (WxDxH)	1200x1000x2200 mm	1200x1000x2350 mm	1300x1100x2300 mm
Gross Weight	360 kg	370 kg	460 kg





Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com